



EC TYPE EXAMINATION (MODULE B)

CERTIFICATE Nr. MED258315CS/002

***This is to certify,** that RINA, specified as Notified Body N° 0474 by the Italian "Ministero delle Infrastrutture e dei Trasporti Direzione Generale per la navigazione ed il Trasporto Marittimo ed Interno" on 25 November 1998, did undertake the relevant type approval procedures for the equipment identified below which was found to be in compliance with the Fire Protection requirements of Marine Equipment Directive (MED) 96/98/EC as modified by Directive 2013/52/EU*

*MED Item N°
Description*

A.1/3.18a

Surface materials and floor coverings with low flame-spread characteristics - (a) decorative veneers

*Type
Applicant*

**FONOSPHERA SF51-10AL
TEKCELL S.P.A.**

VIA DEL CONSORZIO 37
60015 FALCONARA MARITTIMA (AN)
ITALY

*Testing standards
Reference standards*

**IMO Res. MSC.307(88)-(2010 FTP Code)
Chap. II-2 and X of SOLAS 74 Convention, as amended,
RINA Rules for the certification of Marine Equipment**

*Issued at Genoa on
July 31, 2015*

*This Certificate is valid until
July 22, 2020*

This Certificate consists of this sheet plus an attachment



Massimo Dinale

RINA Services S.p.A.



**ATTACHMENT TO
CERTIFICATE Nr. MED258315CS/002
Page 1 of 2**

Manufacturer
TEKCELL S.P.A.

Place of Manufacturer
VIA DEL CONSORZIO 37
60015 FALCONARA MARITTIMA (AN)
ITALY

Product description

Acoustic insulating material composed of :

- 1st layer: cross-linked closed cells polyethylene (thickness 5 mm – mass per area 150 g/m²);
- 2nd layer: polymer based product mixed with mineral fillers;
- 3rd layer: polyester fibre (thickness 10 mm – mass per area 200 g/m²) covered on the external side with an aluminium foil having thickness of 0.05 mm.

Fields of application

As finishing material for all exposed interior and concealed or inaccessible surfaces. When intended for bulkhead and ceiling the product may be applied to any any metallic support having a thickness $\geq 0,75$ mm. When intended for deck the product may be applied to any non-combustible support, any metallic support or any material having low flame spread characteristics.

On the basis of the value of the total heat release (Qt) and on the basis of the value of the peak heat release (Qp) the material is deemed not generating excessive quantities of smoke nor toxic products in fire according to Annex 2 IMO 2010 FTP Code.

Tests carried out

Tests as per RINA Test Laboratory reports Nos. 2010CS012331/2 and 2010CS012331/4 issued respectively on 22 July 2010 and 21 July 2010 according to:

IMO Res. A.653(16)

ISO 1716: 1973




RINA Services S.p.A.
Via Corsica, 12 - 16128 Genova
Tel +39 010 53851
Fax +39 010 5351000



**ATTACHMENT TO
CERTIFICATE Nr. MED258315CS/002
Page 2 of 2**

The mark of conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production control phase module (D, E or F) of Annex B of the Directive is fully complied with a written inspection agreement with a Notified Body




XXXX/YY

"WHEELMARK FORMAT"

XXXX *Notified Body number undertaking surveillance module*
YY *Last two digits of year mark affixed*

General conditions for the approval

- a) The initial conditions verified by RINA at the time of the approval are to be maintained
- b) Any changes to the initial conditions are to be promptly communicated to RINA, which reserves the right to repeat the relevant assessment
- c) This certificate will no be valid if the manufacturer makes any changes or modifications to the approved equipment, which have not been notified to, and agreed with RINA
- d) RINA personnel are to be allowed to witness during the performances of activities, upon their request
- e) The activities are to be carried out in compliance with the RINA Rules and/or other applicable Rules
- f) Should the specified regulations or standards be amended during the validity of this certificate, the product is to be reapproved prior to it being placed on board vessels to which the amended regulations or standards apply.



Massimo Dinale